




The information provided herein is from CONNELY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights contained herein, including but not limited to, trademarks, patents, copyrights, trade secrets, and technical know-how, are owned exclusively by CONNELY or its affiliates. Unauthorized use of any part of this document in any format or manner. CONNELY may enforce its intellectual property rights at its own discretion; failures or delays to exercise such rights does not constitute a waiver of such rights.




Assembled



A Lock Nut




B Washer



C Body



D Seal



E Sealing Nut

Model	Cable Range(mm)	Thread O.D.L1(mm)	Thread Length L2(mm)	Spanner Size A&E(mm)
PG7L	3~6.5	12.3	15	18/16
PG9L	4~8	15.0	15	22/19
PG11L	5~10	18.2	15	24/22
PG13.5L	6~12	20.2	15	27/24
PG16L	10~14	22.2	15	30/27
PG19L	10~15	23.7	15	30/28
PG21L	13~18	28.1	15	36/33
PG25L	16~21	29.7	15	37/35
PG29L	18~25	36.8	15	45/42



(Series Image-Reference Only)

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	JLZ 08/04/23'		
B	DRAWING UPDATE	JLZ 08/25/25'		

Notes:

Specifications:

1. Temperature: -20°C~+80°C.

Materials:

1. Material:Parts A,C,E are made of Nylon or PP;Parts B and D are made of NBR.

Product Number Code:

DS1170-03 - X X X

Materials type

N: Nylon P: PP

Color

A: Gray B: Black

Model

PG7L PG9L

.....

PG29L

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE	Plastic fixed cable gland PG-L type	
X.	±0.60	X.	±5°	UNITS	mm			
.X	±0.38	.X	±3°	SHEET SIZE	A4	SERIES	DS1170-03 SERIES	
.XX	±0.25	.XX	±2°	 晨翔电子有限公司 CONNFLY CONNFLY ELECTRONIC CO. LTD				
DRAWING TYPE		CUSTOMER						
SCALE	1:1	SHEET	1 OF 1					
DRAWING NO.	C-DS1170-03-XXX-B							



晨翔电子有限公司
CONNELY CONNELY ELECTRONIC CO. LTD